INFORMACAST® LOUDSPEAKERS: IP SPEAKER/CLOCKS

Valcom InformaCast® Compliant IP Speakers Enable Live, PreRecorded, Or Ad Hoc Audio Messages To Be Broadcast To Ten People Or Ten Thousand People — Instantly And Economically.

- *PoE (802.3af) - No Local Power Required*
- *2.5" Characters - 5 Character Display*
- *NTP Clock Updates*
- *Atomic Clock Updates*
- *Red LED's - Other LED Colors On Request*
- *Needs Only One Ethernet Port Connection*
- *Output Level 103 db/1Meter*
- *AUX Output Supports Valcom Amplified Speakers*
- *Optional Wall Volume Controls Available*
- *Mounting Backboxes Available*
- *Valcom Offers a Line of Stand Alone IP PoE Clocks, Visit www.valcomclocks.com*

IP SPEAKER/CLOC	ONE-WAY	TALKBACK	BACKBOX TYPE
A. **IP Speaker Faceplate Unit w/Digital Clock** *White*	VIP-419-D-IC	VIP-429-D-IC	22, 23, 24
B. **IP Speaker Surface Mount w/Digital Clock** *Gray w/Black Grille*	VIP-411-DS-IC	VIP-431-DS-IC	N/A
C. **IP Speaker Faceplate Unit w/Digital Clock** *Gray w/Black Grille*	VIP-412-DF-IC	VIP-432-DF-IC	19
D. **IP Speaker Baffle w/12" Analog Clock** *Gray*	N/A	V-CSB12S-IC	20

Backbox Selection Chart

Type	Part No.	Mount Style	Dimensions
19	VB-R19	Recessed	19.25"H x 10.75"W x 3.75"D Grille Hole Dimns.: 10.00" x 18.50"
20	VB-S20	Surface	20.18"H x 14.27"W x 2.78"D Grille Hole Dimns.: 10.50" x 18.50"
21	VB-A21 *Only works with Digital Clocks.*	Angled	19.88"H x 14.27"W x 5.50"D[1] x 2.71"D[2] Grille Hole Dimns.: 10.50" x 18.50"
22	VB-R22	Recessed	13.25"H x 11.25"W x 3.94"D Grille Hole Dimns.: 10.50" x 12.50"
23	VB-S23	Surface	14.63"H x 13.13"W x 3.94"D Grille Hole Dimns.: 10.50" x 12.50"
24	VB-A24	Angled	14.41"H x 13.13"W x 5.00"D[1] x 3.00"D[2] Grille Hole Dimns.: 10.50" x 12.50"

InformaCast® is a Trademark of Singlewire Software.

VALCOM IP